



### **Overview**

- This unit is a power limited power supply/charger that converts a 24VAC / 60Hz plug in Transformer input, into 12VDC output, (refer to specifications).

### **Specifications**

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• 12VDC output.</li> <li>• 1.75 amp supply current.</li> <li>• Class 2 Rated power limited output.</li> <li>• Input 24VAC, 40VA from UL Listed Class 2 direct plug-in transformer.</li> <li>• Filtered and electronically regulated output.</li> <li>• Short circuit and thermal overload protection.</li> <li>• Maximum charge current: 400mA.</li> <li>• Automatic switch over to stand-by battery when</li> </ul> | <ul style="list-style-type: none"> <li>• AC fails (zero voltage drop).</li> <li>• AC fail supervision (form "C" 1 amp @ 28VDC).</li> <li>• Low battery supervision (form "C" 1 amp @ 28VDC).</li> <li>• AC input and DC output LED indicators.</li> <li>• Includes power supply, enclosure and battery leads.</li> <li>• Product weight: 3.3 lbs.</li> <li>• Shipping weight: 3.9 lbs.</li> </ul> |
|---|---|

### **Agency Approvals**



UL Listed Burglar Alarm and Access Control (UL 603, UL 294).

### **Enclosure Dimensions**

8.5"H x 7.5"W x 3.5"D

