



SPECIFICATIONS

SIGNAL SYSTEM	NTSC
SCANNING FREQUENCY (H)	15.734 KHz
SCANNING FREQUENCY (V)	59.94 Hz
SCANNING SYSTEM	2:1 Interlace
IMAGE SENSOR	1/4 Inch SONY Super HAD CCD
TOTAL PIXELS	811(H) x 508(V) 410K
TOTAL / EFFECTIVE PIXELS	768(H) x 494(V) 380K
HORIZONTAL RESOLUTION	480 TV Lines
SIGNAL OUTPUT	1Vp-p Composite Output with 75Ω Terminated
S/N RATIO	More than 48dB (AGC Off)
LENS	22x Zoom Video AF (F=1.6, f=3.9~85.8mm)
DIGITAL ZOOM RATIO	10x (Total Zoom Ratio : Max. 220x), 2x~10x Variable
MIN.ILLUMINATION	Day (1.0Lux), Night(0.001Lux, DSS)
CAMERA CONTROL	Rear Button, RS-485 (Pelco-D)/PTZ Controller Interface
OSD (ON SCREEN DISPLAY)	Built in
DIGITAL SLOW SHUTTER	Off/2FLD~128FLD Mode
SHUTTER SPEED	1/60~1/10,000sec
INPUT/OUTPUT CONNECTOR	Control : 5 Pin Terminal, Power : 2 Pin Terminal, Video : BNC
SUPPLIED VOLTAGE	24VAC / 12VDC Dual Voltage
POWER CONSUMPTION	Max. 5.4W / 450mA
DIMENSIONS	58.00 x 58.00 x 103.40 mm
WEIGHT	Approx. 300g

FEATURES



- 1/4 inch Sony Super HAD CCD
- 22x Optical Power Zoom Lens
- 10x Digital Zoom (220x Zoom)
- Built-in Auto Iris / Auto Focus
- Digital Slow Shutter
- OSD (On Screen Display)
- Video Transmission Distance Adjustable (3 Steps)
- RS-485 (Pelco D) / PTZ controller Interface
- 24VAC/12VDC Dual Voltage