



### SPECIFICATIONS

SIGNAL SYSTEM	NTSC
SCANNING FREQUENCY (H)	15.734 KHz
SCANNING FREQUENCY (V)	59.94 Hz
SCANNING SYSTEM	2:1 Interlace
IMAGE SENSOR	1/3 Inch SONY Super HAD CCD
TOTAL PIXELS	537(H) x 505(V) 270K
TOTAL / EFFECTIVE PIXELS	510(H) x 492(V) 250K
HORIZONTAL RESOLUTION	530 TV Lines
VIDEO OUTPUT	Composite: 1.0V p-p, 75Ω
S/N RATIO	More than 48dB(AGC Off)
LENS	Fixed Lens (f=3.8mm)
MIN.ILLUMINATION	0.3 Lux
WHITE BALANCE	Auto
AGC/BLC/FLICKERLESS	On/Off
SHUTTER SPEED	1/60~1/100,000 sec.
SUPPLIED VOLTAGE	12VDC
POWER CONSUMPTION	Max. 1.8W/150mA
DIMENSIONS (WXH)	85 x 76.7 mm
WEIGHT	Approx. 210g

### FEATURES



- 1/3 inch Sony Super HAD CCD
- High Resolution : 530TV Line
- Built-in Fixed Lens (f=3.8mm)
- Auto White Balance
- AGC, BLC, Flickerless (On/Off)
- Min. Illumination : 0.3 Lux
- Dome Size : 85mm