



### SPECIFICATIONS

SIGNAL SYSTEM	NTSC
SCANNING FREQUENCY (H)	15.734 KHz
SCANNING FREQUENCY (V)	59.94 Hz
SCANNING SYSTEM	2:1 Interlace
IMAGE SENSOR	1/3 Inch SONY Super HAD CCD
TOTAL PIXELS	811(H) x 508(V) 410K
TOTAL / EFFECTIVE PIXELS	768(H) x 494(V) 380K
HORIZONTAL RESOLUTION	550 TV Lines
VIDEO OUTPUT	1.0V p-p (75Ω, Composite)
S/N RATIO	More than 50dB(AGC Off)
LENS	DC Iris Vari-focal Lens (f=4~9mm)
MIN.ILLUMINATION	0.3 Lux
WHITE BALANCE	Auto
AGC,BLC,FLICKERLESS	On/Off (Dip Switch)
SHUTTER SPEED	1/60~1/100,000 Sec
SUPPLIED VOLTAGE	24VAC or 12VDC Dual Voltage
POWER CONSUMPTION	Max. 1.8W/150mA
DIMENSIONS (WXH)	100.0 x 102.0 mm
WEIGHT	Approx. 366g

### FEATURES

- 1/3 inch Sony Super HAD CCD
- High Resolution : 550 TV Lines
- Built in DC Iris Vari-focal Lens (f=4~9mm)
- Auto White Balance
- AGC, BLC, Flickerless (On/Off)
- Min. Illumination : 0.3 Lux
- Extra Video Out Port for Installer
- 3—Axis Camera Construction
- Dome Size : 100mm
- Audio Function (Option)