



SPECIFICATIONS

SIGNAL SYSTEM	NTSC
SCANNING FREQUENCY (H)	15.734 KHz
SCANNING FREQUENCY (V)	59.94 Hz
SCANNING SYSTEM	2:1 Interlace
SYNC. SYSTEM	Internal
IMAGE SENSOR	1/3 Inch SONY Super HAD CCD
TOTAL PIXELS	811(H) x 508(V) 410K
TOTAL / EFFECTIVE PIXELS	768(H) x 494(V) 380K
HORIZONTAL RESOLUTION	530 TV Lines
LENS MOUNT	C/CS Mount
VIDEO OUTPUT	Composite: 1.0V p-p, 75Ω, Unbalanced
S/N RATIO	More than 50dB(AGC Off)
MIN.ILLUMINATION	0.1 Lux(30 IRE, AGC On), 0.0008 Lux (DSS x128)
CAMERA CONTROL	Rear Button, RS-485 (Pelco-D)/PTZ Controller Interface
OSD (ON SCREEN DISPLAY)	On/Off
AGC, BLC	OFF / LOW / MIDDLE / HIGH
COLOR (D&N)	On/Off
DNR	OFF / LOW / MIDDLE / HIGH
SHUTTER SPEED	X128~1/60~1/120,000 Sec.
WHITE BALANCE	ATW (1,800°K~10,500 °K) / AWC / MANUAL
MOTION DECTION	On/Off (4 Programmable Zone)
PRIVACY	On/Off (4 Programmable Zone)
SUPPLIED VOLTAGE	24VAC or 12VDC Dual Voltage
POWER CONSUMPTION	Max. 5.4W / 450mA
DIMENSIONS	62(W) x 58(H) x 123.8(D) mm
WEIGHT	Approx. 430g

FEATURES



- 1/3 inch Sony Super HAD CCD
- High Resolution : 530 TV Lines
- SDNR (Super Digital Noise Reduction)
- OSD (On Screen Display)
- Auto White Balance
- Privacy Zone (On/Off)
- AGC, BLC, Flickerless (On/Off)
- Min : 0.1 Lux (F1.2), 0.0008 Lux (DSSx128)
- AC24V / DC12V Dual Voltage