



SPECIFICATIONS

SIGNAL SYSTEM	NTSC
SCANNING FREQUENCY (H)	15.734 KHz
SCANNING FREQUENCY (V)	59.94 Hz
SCANNING SYSTEM	2:1 Interlace
SYNC. SYSTEM	Internal/External(Line-Lock)
IMAGE SENSOR	1/3 Inch SONY Super HAD CCD
TOTAL / EFFECTIVE PIXELS	410K/380K
IRIS MODE	Video/ELC/DC (Slide Switch)
HORIZONTAL RESOLUTION	480 TV Lines
VIDEO OUTPUT	1.0V p-p (75Ω, Composite)
S/N RATIO	More than 48dB(AGC Off)
MIN.ILLUMINATION	Day (0.3Lux), Night (0.1Lux), DSS (0.001 Lux)
WIDE DYNAMIC RANGE	On/Off
DIGITAL ZOOM RATIO	3x
AGC/BLC/Flickerless	On/Off
DIGITAL SLOW SHUTTER	Off/2FLD~160FLD Mode
DAY&NIGHT(ICR)	Auto/Day/Night (Sensor 1EA)
SHUTTER SPEED	1/60~1/10,000 sec
WHITE BALANCE	Auto / Hold / Manual
CAMERA ID/ZONE LABEL	On/Off
MIRROR/FREEZE/NAGATIVE	On/Off
SUPPLIED VOLTAGE	24VAC (20V~28V) / 12VDC (10V~15V)
POWER CONSUMPTION	Max. 7.2W / 600mA
DIMENSIONS(WxHxD)	64 x 57.6 x 124.6mm
WEIGHT	Approx. 430g

FEATURES



- 1/3 inch Sony Double Scan CCD
- High Resolution : 480 TV Lines
- TDN(ICR), 3x Digital Zoom
- Min. Illumination : 0.0003Lux (DSS On, B/W)
- OSD(On Screen Display), Auto White Balance
- AGC(Low/Middle/High), BLC/Flickerless (On/Off)
- WDR (Wide Dynamic Range), Privacy Zone
- RS-485(Pelco-D) Interface
- Electronic Sensitivity-up(DSS)
- 24VAC/12VDC Dual Voltage(Line-Lock)