



V1310NIR

IR VANDAL-RESISTANT DOME CAMERA



SPECIFICATIONS

SIGNAL SYSTEM	NTSC
SCANNING SYSTEM	2:1 Interlace
SCANNING FREQUENCY (H)	15.734 KHz
SCANNING FREQUENCY (V)	59.94 Hz
IMAGE SENSOR	1/3 Inch SONY Super HAD CCD
TOTAL PIXELS	811(H) x 508(V) 410K
TOTAL / EFFECTIVE PIXELS	768(H) x 494(V) 380K
HORIZONTAL RESOLUTION	550 TV Lines
VIDEO OUTPUT	1.0V p-p (75Ω, Composite)
S/N RATIO	More than 50dB(AGC Off)
IR LED & SENSOR	Built in 24EA IR LED (850nm, 30°) & 1EA Sensor
IR VISIBLE RANGE	Max. 15m
LENS	Fixed Lens (f=3.8mm)
MIN.ILLUMINATION	Day (0.3 Lux), Night(0.00 Lux, IR LED On)
WHITE BALANCE	Auto
AGC,BLC,FLICKERLESS	On/Off (Dip Switch)
OSD	On/Off
PRIVACY ZONE	On/Off(4 Programmable Zone)
MOTION DETECTION	On/Off(64 Programmable Zone)
SHUTTER SPEED	1/60~1/100,000 Sec.
SUPPLIED VOLTAGE	12VDC
DIMENSIONS(ØXH)	100.0 x 101.0 mm
WEIGHT	Approx. 844g

FEATURES



- 1/3 inch Sony Super HAD CCD
- High Resolution : 550 TV Lines
- Built-in Fixed Lens (f=3.8mm)
- Auto White Balance
- AGC, BLC, Flickerless (On/Off)
- Motion Detection
- Privacy Zone
- 24EA IR LED, 1EA Sensor
- Min. Illumination : Night (0.00 Lux, IR LED On)
- Extra Video Out Port for Installer
- 3-Axis Camera Construction
- Built-in Heater (Option), Camera Bracket (Option)
- Diameter of Bubble : 100mm

Visit us:
www.norelcotele.com
sales@norelcotele.com

Norelco Safecam

27 Armthorpe Road
 Brampton, Ontario, L6T 5M4
 Phone: (905) 790-1234
 Toll Free: (800) 668-3402
 Fax: (905) 790-1122