



### SPECIFICATIONS

SIGNAL SYSTEM	NTSC
SCANNING SYSTEM	2:1 Interlace
SCANNING FREQUENCY (H)	15.734 KHz
SCANNING FREQUENCY (V)	59.94 Hz
IMAGE SENSOR	1/3 Inch SONY Super HAD CCD
TOTAL PIXELS	811(H) x 508(V) 410K
TOTAL / EFFECTIVE PIXELS	768(H) x 494(V) 380K
HORIZONTAL RESOLUTION	550 TV Lines
VIDEO OUTPUT	1.0V p-p (75Ω, Composite)
S/N RATIO	More than 50dB(AGC Off)
LENS	DC Iris Vari-focal Lens (f=3.8~9.5mm)
DIGITAL ZOOM RATIO	2x (On/Off, Dip Switch)
MIN.ILLUMINATION	Day (0.3 Lux), Night(0.001, ICR&DSS)
DAY&NIGHT (ICR)	On/Off (Dip Switch)
SDNR	Built-in
DSS	On/Off (Dip Switch)
WHITE BALANCE	Auto
AGC,BLC,FLICKERLESS	On/Off (Dip Switch)
SHUTTER SPEED	1/60~1/120,000 Sec.
SUPPLIED VOLTAGE	24VAC or 12VDC Dual Voltage
POWER CONSUMPTION	Max. 1.8W / 150mA
HEATER (OPTION)	Operation Temperature : Under 10
DIMENSIONS(ØXH)	Surface : 100.0 x 124.5 mm Flush : 100.0 x 111.0 mm
WEIGHT	Approx. 1210g

### FEATURES



- 1/3 inch Sony Super HAD CCD
- High Resolution : 550 TV Lines
- Built in DC Iris Vari-focal Lens (f=3.8~9.5mm)
- TDN(ICR), 2x Digital Zoom (On/Off)
- Electronic Sensitivity-up (DSS On/Off)
- SDNR (Super Digital Noise Reduction)
- Auto White Balance
- AGC, BLC, Flickerless (On/Off)
- Min : Day (0.3Lux), Night(0.001Lux, ICR&DSS)
- Extra Video Out Port for Installer
- 3—Axis Camera Construction
- Vandal-proof Dome Housing
- Dome Size : 100mm
- Heater Optional