



### SPECIFICATIONS

SIGNAL SYSTEM	NTSC
SCANNING SYSTEM	2:1 Interlace
SYNC. SYSTEM	Internal/External (Line-Lock)
IMAGE SENSOR	1/3 Inch SONY Super HAD CCD
TOTAL / EFFECTIVE PIXELS	410K/380K
HORIZONTAL RESOLUTION	530 TV Lines
VIDEO OUTPUT	Composite: 1.0V p-p, 75Ω, Unbalanced
S/N RATIO	More than 50dB (AGC Off)
LENS	DC Iris Vari-focal Lens (f=4~9mm)
MIN.ILLUMINATION	0.1Lux (Color), 0.0008Lux (DSS On, B/W)
DAY&NIGHT	Electronic Sensitivity-up(DSS)
SDNR	Off / Low / Middle / High
OSD	On / Off
DIGITAL SLOW SHUTTER	Max. 128FLD (On/Off)
PRIVACY ZONE	ON / Off (4 Programmable Zone)
MOTION DETECTION	On / Off (4 Programmable Zone)
MIRROR FUNCTION	On / Off (Horizontal)
SHARPNESS CONTROL	On / Off (Level Adjustable)
WHITE BALANCE	On/Off (Dip switch)
AGC/BLC/FLICKERLESS	Auto
SHUTTER SPEED	1/60~1/120,000 sec
SUPPLIED VOLTAGE	24VAC or 12VDC Dual Voltage
POWER CONSUMPTION	Max. 4W / 330mA
CAMERA CONSTRUCTION	3-Axis Movement for Free Lens Rotation
DIMENSIONS(ØXH)	100.0 x 124.5 mm
WEIGHT	Approx. 1210g

### FEATURES

- 1/3 inch Sony Super HAD CCD
- High Resolution : 530 TV Lines
- Built-in DC Iris Vari-focal Lens(f=4~9mm)
- Min. Illumination : 0.0008Lux (DSS on, B/W)
- SDNR (Super Digital Noise Reduction)
- OSD(On Screen Display), Privacy Zone
- Electronic Sensitivity-up(DSS) (On/Off)
- Polycarbonate dome & die casting housing
- Extra Video Out Port for Installer
- 3-Axis Movement for Free Lens Rotation
- Dome Size 100mm,
- Dual(Surface/Flush) Mount
- Built-in Heater(Optional)