



VB2310NIR

EYE BALL VANDAL IR DOME



SPECIFICATIONS

SIGNAL SYSTEM	NTSC
SCANNING SYSTEM	2:1 Interlace
SCANNING FREQUENCY (H)	15.734 KHz
SCANNING FREQUENCY (V)	59.94 Hz
IMAGE SENSOR	1/3 Inch SONY Super HAD CCD
TOTAL PIXELS	811(H) x 508(V) 410K
TOTAL / EFFECTIVE PIXELS	768(H) x 494(V) 380K
HORIZONTAL RESOLUTION	550 TV Lines
VIDEO OUTPUT	1.0V p-p (75Ω, Composite)
S/N RATIO	More than 48dB(AGC Off)
IR LED & SENSOR	Built in 35EA IR LED (850nm, 30°) & 1EA Sensor
IR VISIBLE RANGE	Max. 25m
LENS	Fixed Lens (f=6mm)
MIN.ILLUMINATION	0 Lux (IR LED On)
WHITE BALANCE	Auto
AGC	Auto
SHUTTER SPEED	1/60
SUPPLIED VOLTAGE	12VDC
POWER CONSUMPTION	700mA (Max. 9W)
DIMENSIONS (ØXH)	124 x 96
WEIGHT	Approx. 848g

FEATURES

- 1/3 inch Sony Super HAD CCD
- High Resolution : 550 TV Lines
- Built-in Fixed Lens(f=6mm)
- Built-in IR LED(35EA) & Sensor(1EA)
- Min. Illumination : 0 Lux (IR LED On)
- Eye Ball Size 96mm
- Vandal-Resistant Housing
- 12VDC

Visit us:
www.norelcotele.com
sales@norelcotele.com

Norelco Safecam

27 Armthorpe Road
Brampton, Ontario, L6T 5M4
Phone: (905) 790-1234
Toll Free: (800) 668-3402
Fax: (905) 790-1122