



SPECIFICATIONS

Signal System	NTSC
Scanning System	2:1 Interlace
Sync. System	Internal
Image Sensor	1/4 Inch SONY Super HAD CCD
Total / Effective Pixels	410K/380K
Horizontal Resolution	480 TV Lines
Video Output	Composite: 1.0V p-p, 75Ω, Unbalanced
S/N Ratio	More than 48dB (AGC Off)
Lens	22x Optical Zoom (F=1.6, f=3.9~85.8mm) Video AF
Digital Zoom Ratio	10x(Total Zoom Ratio : Max. 220x), 2x~10x Variable
Min.Illumination	Day (1.0Lux), Night (0.001Lux, DSS)
Camera Control	RS-485 (Pelco-D) Interface, Key Button
OSD	Built-in
Digital Slow Shutter	Off/2FLD~128FLD Mode
Shutter Speed	1/60~1/10,000 Sec.
Input/Output Connector	Power : 2 Pin Terminal, Video : BNC/RCA
Supplied Voltage	24VAC or 12VDC Dual Voltage
Power Consumption	Max. 15W
Heater (Option)	Operation Temperature : Under 10 °C
Dimensions (ØxH)	119.80 x 126.50 mm
Weight	Approx. 1.6 Kg

FEATURES

- 1/3 inch Sony Super HAD CCD
- High Resolution : 530 TV Lines
- Built-in Fixed Lens (f=3.8mm)
- Min. Illumination : 0.3 Lux
- Auto White Balance (AWB)
- Auto Gain Control (AGC)
- Dome Size 55mm
- Vandal-Resistant Housing
- 12VDC