



# XN95SH-H12KD

## HIGH RESOLUTION IR LED NIGHTVIEW CAMERA



### SPECIFICATIONS

IMAGE SENSOR	1/3" SONY SUPER HAD High Resolution (410K Pixels.)
H. RESOLUTION/SCANNING SYSTEM	NTSC/PAL - 500TVL 10Bit (2:1 Interlaced) NTSC(525TVL) : 768 x 494, PAL(625TVL) : 752 x 582
MIN. ILLUMINATION	0.05Lux (IR LED Off)
SCANNING FREQUENCY	Horizontal:15,734Hz, Vertical:59.94Hz
VIDEO OUTPUT LEVEL	1.0Vp-p (75ohms, Composite)
S/N RATIO	More than 50dB (AGC Off)
GAMMA	r = 0.45 or More
WHITE BALANCE	2,100°K - 9500°K - Auto
GAIN CONTROL	4dB - 35dB - Auto
IR LED CAPABILITY	Visible 10mm, 200mA Diameter (850nm, 14°) x 42ea Exchanged Angle of IR LD by Lens Angle of View
VISIBILITY RANGE	Real 80 Meter ( Approx. 240 Feet )
CDS CONTROL	IR Cut Filtered CDS Controlled IR LED On/Off at 10 Lux
COLOR/BW CONTROL	True Color at Day time & True B/W at Night time DIET™ - Digital 10 Bit Image-Enhanced Technology for 500TV Lines
OPERATING TEMPERATURE (HUMIDITY)	- 20 °C - +60 °C (10% - 95% RH, IP Rating=67)
LENS	STD Lens : f = 12.0mm IR Lens (AOV : 39°) 4mm / 6mm / 8mm IR Exclusive LENS (F1.4)
MTTF (AVERAGE LIFE)	80,000 Hour or More
POWER SOURCE	Max. 980mA / 1Amp Regulated preferred (Normal) DC12V (Tolerance : 8V ~ 35V) / AC 24V (Tolerance : 18V ~ 48V)
DIMENSIONS (WXHXD/MM)	163.0 x 102.0 x 101.0 (w/Sunshield)
NET WEIGHT	1.12kg (w/Sunshield) - 39.50oz

### FEATURES

- World first 10mm dia. 200mA Visible 850nm Twin-Plate IR LED x 42ea Built-in ( Visibility Range : Real 80M ( Approx. 240Feet ) )
- 1/3" SONY SUPER HAD 500TVL High Resolution Image Sensor Built-in (Min Illumination : 0.05Lux (LED OFF))
- Color at Day Time and B/W at Night time controlled by CDS Sensor without noise
- Dynamic IR LED ON/OFF controlled by Digitalized CDS Sensor - No missed malfunctions at dawn, dusk or any twilight time
- IR Exclusive high quality 12mm lens built-in for anti focus shift (F1.4)
- DIET™ - Digital 10 Bit Image-Enhanced Technology for High picture quality 500TV Lines
- DAIL™ - Dual Anti-IR LED reflection Front Cover Glass
- Perfect interception from IR LED reflection & 100% isolation of Camera Lens from IR LED diffused reflection
- BBAR(Broad Band Anti-Reflection) Coated Front Cover Glass for Perfect Permeation of IR LED
- IR LED CUT Coated CDS Sensor Built-in - Sensoring all of spectrum precisely and automatically
- IR LED Temperature Feed back Circuit - Advanced IR LED Protection through control Electronic Current

Visit us:  
[www.norelcotele.com](http://www.norelcotele.com)  
[sales@norelcotele.com](mailto:sales@norelcotele.com)

### Norelco Safecam

27 Armthorpe Road  
 Brampton, Ontario, L6T 5M4  
 Phone: (905) 790-1234  
 Toll Free: (800) 668-3402  
 Fax: (905) 790-1122